


Article number/ Available dimensions:	309030010 – 45/60/45 309040010 – 65/95/65	
Product name:	Flexible duct connectors - Fibreglass/Neoprene	
Description:	The flexible duct connector consist of neoprene coated fiberglass fabric. The fabric is enclosed between two galvanized steel sheets. The connection guarantees a lasting hold and persistent air tightness. The fold is interrupted at regular intervals, which simplify the bending and forming of the duct connectors.	
Fabric:	Fibreglass	
Coating:	Neoprene	
Colour:	Black	
Unit:	Rolls a 25 m	
Weight:	fabric: approx. 410 gr./m <sup>2</sup> - coating: approx. 2 x 125 gr./m <sup>2</sup>	
Temperature resistance	-20°C / +100 °C	
Fire resistance	M1 / BS 476 Part 7 Class 1	
Properties:	Very good mechanical resistance UV-resistant	
Steel tape:	Galvanized steel - thickness: 0,4 mm	

The intention of this product leaflet is to provide non-binding information and should only be interpreted as such. The information takes the current state of technical developments and developments in the chemical industry. We reserve the right to make modifications relating to the product as well as to develop it further. No liability on our part can be derived from this. Users should check the suitability of the product for the intended purpose by conducting their own tests.

Dimensions:	Fabric/material: 60, 95, mm Sheet metal: 45, 65 mm
Remarks:	<ul style="list-style-type: none"><li>• Free from silicone</li><li>• Free from cadmium</li></ul> <p>Comply with the requirements of BS 476 Part 7 (Rated class 1) Tested to DIN EN 1507 – Class C (TÜV-Nord certified)</p>