## **GEBHARDT** STAHL

PRODUCT DATA SHEET - 315XXX010

Gebhardt-Stahl GmbH

Tel. +49 2922 9733-0 info@gebhardt-stahl.de

Runtestraße 33 59457 Werl Postfach 80 35 59079 Werl Fax +49 2922 9733-290 www.gebhardt-stahl.de

As of: 18.05.2021

Article number/ Nominal width:	315590010 - 450 mm 315600010 - 500 mm 315610010 - 560 mm 315615010 - 600 mm 315620010 - 630 mm 315630010 - 710 mm 315640010 - 800 mm 315650010 - 900 mm 315660010 - 1000 mm 315670010 - 1120 mm 315680010 - 1250 mm
Product name:	GEBHARDT Clamp for spiral-seam tubes
Field of application:	Assembling system for spiral-seam tubes / circular ductwork
Material:	Galvanized steel
Measurement:	width: 25 mm thickness: 2,5 mm
Locking screw:	M 10 x 25 mm
Nominal width:	450 mm – 1250 mm
Properties:	<ul> <li>2-part screw fixed pipe clamp with a welded on combination nut M8/M10</li> <li>sound insulation enclosure inserted in a positive lock</li> <li>EPDM quality for DIN 4109</li> <li>insulation rubber: silicone and halogen free</li> <li>temperature resistant -30 °C to +70/80 °C</li> <li>quick and practice- oriented installation as a result of wide opening angles</li> <li>matches pipe tolerances as a result of 2 locking screws</li> <li>Maximal load per pipe clamp app. 100 kg (central fixing)</li> <li>Maximal load per pipe clamp app. 200 kg (lateral fixing)</li> </ul>
Weight:	450 mm: 0,90 kg/pc 630 mm: 1,20 kg/pc 1000 mm: 2,20 kg/pc 500 mm: 1,00 kg/pc 710 mm: 1,35 kg/pc 1120 mm: 2,40 kg/pc 560 mm: 1,05 kg/pc 800 mm: 1,70 kg/pc 1250 mm: 2,60 kg/pc 600 mm: 1,15 kg/pc 900 mm: 2,00 kg/pc

The intention of this product leaflet is to provide non-binding information and should only be interpreted as such. The information takes the current state of technical developments and developments in the chemical industry. We reserve the right to make modifications relating to the product as well as to develop it further. No liability on our part can be derived from this. Users should check the suitability of the product for the intended purpose by conducting their own tests.