


Article number:	310100000 – 9 x 4 mm 310110000 – 12 x 4 mm 310070000 – 15 x 4 mm 310160000 – 20 x 4 mm 310170000 – 25 x 4 mm 310140000 – 12 x 5 mm 310015000 – 9 x 6 mm 310060000 – 15 x 6 mm 						
Product name:	Gebhardt Sealing tape						
Material:	Polyethylene foam						
Colour:	Grey						
Adhesive:	Synthetic rubber hot-melt						
Liner:	No liner						
Peel adhesion:	DIN EN 1939                      material break						
Temperature range:	-30 °C to +80 °C						
Resistance to high humidity:	Very good						
Density:	ISO 845                                      ~ 30 kg/m <sup>3</sup>						
Tensile strength:	<table border="0"> <tr> <td>ISO 1926</td> <td>lengthwise</td> <td>325 kPa</td> </tr> <tr> <td></td> <td>crosswise</td> <td>220 kPa</td> </tr> </table>	ISO 1926	lengthwise	325 kPa		crosswise	220 kPa
ISO 1926	lengthwise	325 kPa					
	crosswise	220 kPa					
Elongation at break:	<table border="0"> <tr> <td>ISO 1926</td> <td>lengthwise</td> <td>125 %</td> </tr> <tr> <td></td> <td>crosswise</td> <td>115 %</td> </tr> </table>	ISO 1926	lengthwise	125 %		crosswise	115 %
ISO 1926	lengthwise	125 %					
	crosswise	115 %					

The intention of this product leaflet is to provide non-binding information and should only be interpreted as such. The information takes the current state of technical developments and developments in the chemical industry. We reserve the right to make modifications relating to the product as well as to develop it further. No liability on our part can be derived from this. Users should check the suitability of the product for the intended purpose by conducting their own tests.

Compressive strength at 50 % compression:	ISO 844	98 kPa
Compression set 25 % / 22 h at 23°C:	ISO 1856-B	20 % (0,5 h after discharge) 12 % ( 24 h after discharge)
Water absorption (7 d):	< 1 Vol.-%	
Weight:	9 x 4 mm: 0,0021 kg/m 12 x 4 mm: 0,0028 kg/m 15 x 4 mm: 0,0033 kg/m 20 x 4 mm: 0,0045 kg/m 25 x 4 mm: 0,0060 kg/m 12 x 5 mm: 0,0030 kg/m 9 x 6 mm: 0,0035 kg/m 15 x 6 mm: 0,0042 kg/m	
Certificates/Tests:	Tested to DIN EN ISO 846 (suitable for use in ventilation systems according to VDI 6022)	
Delivery unit:	9 x 4 mm: Rolls á 10 m, PU á 2.400 m, pallet á 24.000 m 12 x 4 mm: Rolls á 10 m, PU á 1.800 m, pallet á 18.000 m 15 x 4 mm: Rolls á 10 m, PU á 1.500 m, pallet á 15.000 m 20 x 4 mm: Rolls á 10 m, PU á 1.100 m, pallet á 11.000 m 25 x 4 mm: Rolls á 10 m, PU á 900 m, pallet á 9.000 m 12 x 5 mm: Rolls á 10 m, PU á 1.820 m, pallet á 18.200 m 9 x 6 mm: Rolls á 10 m, PU á 330 m, pallet á 13.200 m 15 x 6 mm: Rolls á 10 m, PU á 1.000 m, pallet á 10.000 m	
Remarks:	<ul style="list-style-type: none"> <li>• Free of paint-wetting impairment substances (PWIS- / LABS-free)</li> <li>• Silicone-free</li> <li>• Halogen-free</li> <li>• Lead-free</li> <li>• Cadmium-free</li> <li>• Chrome 6-free</li> </ul>	