

Article number:	310090000 – 10 x 6 mm 310080000 – 15 x 6 mm	
Product name:	Ceramic Sealing tape	
Description:	Resistant self-adhesive fibreglass tape for sealing duct joints. Suitable for use in fire-rated and smoke extraction ductwork	
Material:	Fibreglass	
Fiber diameter:	Ø 3,2 µm	
Adhesive:	Acryl-Dispersion	
Colour:	White	
Lidding material:	PE-Silicone film	
Adhesive bonder	Nonwoven-fleece	
Classification temperature:	+ 1200 °C	
Melting point:	> 1330 °C	
Density:	180 – 240 kg/m ³	
Tensile strength:	> 350 kPa	
Properties:	<ul style="list-style-type: none">● one-sided self-adhesive● solvent-free● asbestos-free	

The intention of this product leaflet is to provide non-binding information and should only be interpreted as such. The information takes the current state of technical developments and developments in the chemical industry. We reserve the right to make modifications relating to the product as well as to develop it further. No liability on our part can be derived from this. Users should check the suitability of the product for the intended purpose by conducting their own tests.

Delivery unit:	10 x 6 mm: Roles à 10 m, box à 300 m, pallet à 12.000 m 15 x 6 mm: Roles à 10 m, box à 200 m, pallet à 8.000 m
Remarks:	Due to the excellent biosolubility, the intilized fibreglass is classified as non-carcinogenic